

Citrix ADC Hardware Platforms

Enabling high performance application delivery with hardware appliances and multi-tenant support

Citrix Application Delivery Controller (ADC) is the most comprehensive application delivery and load balancing solution for multi-cloud environments. Because its software and hardware form factors are all built on a single code base, Citrix ADC provides operational and feature consistency with comprehensive security for monolithic and microservices-based applications on-premises and in the cloud.

With pooled capacity licensing, you can easily move capacity across Citrix ADC form factors, clouds, and geographies to meet growing demand with no issues.

[Citrix Application Delivery Management \(ADM\)](#) helps you achieve holistic visibility, management, and troubleshooting for your entire Citrix ADC fleet through a single, easy to use console.

Citrix ADC Hardware Platforms

Citrix ADC MPX

Citrix ADC MPX is a physical appliance that provides powerful hardware-based application delivery and load balancing with options for high performance web application security and SSL offload support.

Citrix ADC SDX

Citrix ADC SDX introduces fully isolated multi-tenant support on a single appliance for application workloads and groups. Deploying multiple virtual instances of Citrix ADC on one hardware appliance allows for the consolidation of multiple load balancers and application rollout.

Citrix ADC FIPS Platforms

Citrix ADC offers specific physical and virtual platforms with FIPS 140-2 compliance to meet the strict compliance mandates of high security businesses and organizations.

Learn more about the specific Citrix ADC FIPS platforms by visiting the [Citrix ADC FIPS Platforms data sheet](#).

Citrix ADC Platform	MPX/SDX 26200-100G	MPX/SDX 26160-100G	MPX/SDX 26100-100G
Attributes			
Memory	256 GB	256 GB	256 GB
Ethernet Ports ¹	8x 100GE QSFP28	8x 100GE QSFP28	8x 100GE QSFP28
Transceivers Support	50GE/100GE QSFP28: SR4; 40GE QSFP+: SR4; 25GE SFP28: SR (Adapter required); 10GE SFP+: SR, LR (Adapter required)		
RAID Support	Yes	Yes	Yes
Pay-as-you-grow & Burst Pack License Upgrades	-	Upgrade option to MPX/SDX 26200-100G	Upgrade option to MPX/SDX 26200, 160-100G
Performance			
System Throughput (Gbps) [L7 Throughput]	200	160	100
L7 HTTP Requests/sec	5,500,000	4,200,000	3,200,000
SSL Transactions/sec (2K Key Certificates) ²	125,000	110,000	66,000
ECDHE Transactions/sec	58,000	50,000	30,000
SSL Throughput (Gbps)	60	48	36
Compression Throughput (Gbps)	18	15	12
ICA Proxy/SSL VPN Concurrent Users	20,000	20,000	20,000
Included Instances, Maximum Instances (on SDX Platforms)	115, 115	70, 115	20, 115
Mechanical, Environmental, and Regulatory			
Power Supplies	2	2	2
Input Voltage, Frequency Range	100-240 VAC full range, 50-60 Hz	100-240 VAC full range, 50-60 Hz	100-240 VAC full range, 50-60 Hz
Optional DC Power Supply	Yes	Yes	Yes
Max Power Supply	822W	822W	822W
Typical, Max Power Consumption	300W, 1024 BTU/Hr	300W, 1024 BTU/Hr	300W, 1024 BTU/Hr
Weight (lbs)	48	48	48
Height	2U	2U	2U
Width	EIA 310-D, IEC 60297, DIN 41494 SC48D rack width with mounting brackets		
Depth	71.1 cm (28 in)	71.1 cm (28 in)	71.1 cm (28 in)
Operating Temperature	0-45°C (32-113°F)	0-45°C (32-113°F)	0-45°C (32-113°F)
Allowed Relative Humidity	5%-95%, Non-condensing	5%-95%, Non-condensing	5%-95%, Non-condensing
Safety Certifications	IEC 60950-1, 2nd Edition; CSA 60950-1, 2nd Edition; UL 60950-1, 2nd Edition; AS/NZS 60950-1		
Electromagnetic Emissions Certifications & Susceptibility Standard	US (FCC (Part 15 Class A)), Europe (CE (EN 55032/55024)), Australia (RCM), Japan (VCCI), Korea (KCC), Taiwan (BSMI), China (CCC), India (BIS), Russia (CUTR), Russia (EAC), Saudi Arabia (CITC), Brazil (Anatel), South Africa (ICASA), Mexico (NOM), Egypt (NTRA), Israel (MoC)		
Regulatory Compliance	RoHS, WEEE, REACH		
Citrix Compliance Regulatory Model	2U1P1D	2U1P1D	2U1P1D

1. Published Ethernet interfaces compliant per IEEE802.3-2002/2005/2008/2012.

2. Performance varies depending on ciphers deployed. Contact your Citrix sales representative for details.

Citrix ADC Platform	MPX/SDX 26200-50S	MPX/SDX 26160-50S	MPX/SDX 26100-50S
Attributes			
Memory	256 GB	256 GB	256 GB
Ethernet Ports ¹	4x 50GE QSFP28; 16x 25GE SFP28		
Transceivers Support	50GE QSFP28 Port: 50GE/100GE QSFP28: SR4; 40GE QSFP+: SR4; 25GE SFP28: SR (Adapter required); 10GE SFP+: SR, LR (Adapter required) 25GE SFP28 Port: 25GE SFP28: SR; 10GE SFP+: SR, LR		
RAID Support	Yes	Yes	Yes
Pay-as-you-grow & Burst Pack License Upgrades	-	Upgrade option to MPX/SDX 26200-50S	Upgrade option to MPX/SDX 26200, 160-50S
Performance			
System Throughput (Gbps) [L7 Throughput]	200	160	100
L7 HTTP Requests/sec	6,500,000	5,500,000	4,500,000
SSL Transactions/sec (2K Key Certificates) ²	522,000	358,000	283,000
ECDHE Transactions/sec	230,000	165,000	120,000
SSL Throughput (Gbps)	120	100	80
Compression Throughput (Gbps)	22	16	13
ICA Proxy/SSL VPN Concurrent Users	20,000	20,000	20,000
Included Instances, Maximum Instances (on SDX Platforms)	115, 115	70, 115	20, 115
Mechanical, Environmental, and Regulatory			
Power Supplies	2	2	2
Input Voltage, Frequency Range	100-240 VAC full range, 50-60 Hz	100-240 VAC full range, 50-60 Hz	100-240 VAC full range, 50-60 Hz
Optional DC Power Supply	No	No	No
Max Power Supply	1200W	1200W	1200W
Typical, Max Power Consumption	628W, 764W	628W, 764W	628W, 764W
Weight (lbs)	48	48	48
Height	2U	2U	2U
Width	EIA 310-D, IEC 60297, DIN 41494 SC48D rack width with mounting brackets		
Depth	71.1 cm (28 in)	71.1 cm (28 in)	71.1 cm (28 in)
Operating Temperature	0-45°C (32-113°F)	0-45°C (32-113°F)	0-45°C (32-113°F)
Allowed Relative Humidity	5%-95%, Non-condensing	5%-95%, Non-condensing	5%-95%, Non-condensing
Safety Certifications	IEC 60950-1, 2nd Edition; CSA 60950-1, 2nd Edition; UL 60950-1, 2nd Edition; AS/NZS 60950-1		
Electromagnetic Emissions Certifications & Susceptibility Standard	US (FCC (Part 15 Class A)), Europe (CE (EN 55032/55024)), Australia (RCM), Japan (VCCI), Korea (KCC), Taiwan (BSMI), China (CCC), India (BIS), Russia (CUTR), Russia (EAC), Saudi Arabia (CITC), Brazil (Anatel), South Africa (ICASA), Mexico (NOM), Egypt (NTRA), Israel (MoC)		
Regulatory Compliance	RoHS, WEEE, REACH		
Citrix Compliance Regulatory Model	2U1P2A	2U1P2A	2U1P2A

1. Published Ethernet interfaces compliant per IEEE802.3-2002/2005/2008/2012.

2. Performance varies depending on ciphers deployed. Contact your Citrix sales representative for details.

Citrix ADC Platform	MPX 26200T-100G	MPX 26160T-100G	MPX 26100T-100G
Attributes			
Memory	256 GB	256 GB	256 GB
Ethernet Ports ¹	8x 100GE QSFP28	8x 100GE QSFP28	8x 100GE QSFP28
Transceivers Support	50GE/100GE QSFP28: SR4; 40GE QSFP+: SR4; 25GE SFP28: SR (Adapter required); 10GE SFP+: SR, LR (Adapter required)		
RAID Support	Yes	Yes	Yes
Pay-as-you-grow & Burst Pack License Upgrades	-	Upgrade option to MPX 26200T-100G	Upgrade option to MPX 26200T, 160T-100G
Performance			
System Throughput (Gbps) [L7 Throughput]	200	160	100
L7 HTTP Requests/sec	5,500,000	4,200,000	3,200,000
SSL Transactions/sec (2K Key Certificates) ²	N/A	N/A	N/A
ECDHE Transactions/sec ³	N/A	N/A	N/A
SSL Throughput (Gbps)	N/A	N/A	N/A
Compression Throughput (Gbps)	18	15	12
ICA Proxy/SSL VPN Concurrent Users	20,000	20,000	20,000
Included Instances, Maximum Instances (on SDX Platforms)	N/A	N/A	N/A
Mechanical, Environmental, and Regulatory			
Power Supplies	2	2	2
Input Voltage, Frequency Range	100-240 VAC full range, 50-60 Hz	100-240 VAC full range, 50-60 Hz	100-240 VAC full range, 50-60 Hz
Optional DC Power Supply	Yes	Yes	Yes
Max Power Supply	822W	822W	822W
Typical, Max Power Consumption	300W, 1024 BTU/Hr	300W, 1024 BTU/Hr	300W, 1024 BTU/Hr
Weight (lbs)	48	48	48
Height	2U	2U	2U
Width	EIA 310-D, IEC 60297, DIN 41494 SC48D rack width with mounting brackets		
Depth	71.1 cm (28 in)	71.1 cm (28 in)	71.1 cm (28 in)
Operating Temperature	0-45°C (32-113°F)	0-45°C (32-113°F)	0-45°C (32-113°F)
Allowed Relative Humidity	5%-95%, Non-condensing	5%-95%, Non-condensing	5%-95%, Non-condensing
Safety Certifications	IEC 60950-1, 2nd Edition; CSA 60950-1, 2nd Edition; UL 60950-1, 2nd Edition; AS/NZS 60950-1		
Electromagnetic Emissions Certifications & Susceptibility Standard	US (FCC (Part 15 Class A)), Europe (CE (EN 55032/55024)), Australia (RCM), Japan (VCCI), Korea (KCC), Taiwan (BSMI), China (CCC), India (BIS), Russia (CUTR), Russia (EAC), Saudi Arabia (CITC), Brazil (Anatel), South Africa (ICASA), Mexico (NOM), Egypt (NTRA), Israel (MoC)		
Regulatory Compliance	RoHS, WEEE, REACH		
Citrix Compliance Regulatory Model	2U1P1D	2U1P1D	2U1P1D

1. Published Ethernet interfaces compliant per IEEE802.3-2002/2005/2008/2012.

2. Performance varies depending on ciphers deployed. Contact your Citrix sales representative for details.

3. Hybrid SSL optimization (TLS1-ECDHE-RSA-AES182-SHA 256)

Citrix ADC Platform	MPX/SDX 26200	MPX/SDX 26160	MPX/SDX 26100
Attributes			
Memory	256 GB	256 GB	256 GB
Ethernet Ports ¹	8x 50GE QSFP28; 16x 25G SFP28		
Transceivers Support	50GE QSFP28 Port: 50GE/100GE QSFP28: SR4; 40GE QSFP+: SR4; 25GE SFP28: SR (Adapter required); 10GE SFP+: SR, LR (Adapter required); 25GE SFP28 Port: 25GE SFP28: SR; 10GE SFP+: SR, LR		
RAID Support	Yes	Yes	Yes
Pay-as-you-grow & Burst Pack License Upgrades	-	Upgrade option to MPX/SDX 26200	Upgrade option to MPX/SDX 26200, 26160
Performance			
System Throughput (Gbps) [L7 Throughput]	200	160	100
L7 HTTP Requests/sec	5,400,000	4,300,000	3,800,000
SSL Transactions/sec (2K Key Certificates) ²	310,000	220,000	140,000
ECDHE Transactions/sec	130,000	90,000	60,000
SSL Throughput (Gbps)	80	64	51
Compression Throughput (Gbps)	22	17	13
ICA Proxy/SSL VPN Concurrent Users	20,000	20,000	20,000
Included Instances, Maximum Instances (on SDX Platforms)	115, 115	70, 115	20, 115
Mechanical, Environmental, and Regulatory			
Power Supplies	2	2	2
Input Voltage, Frequency Range	100-240 VAC full range, 50-60 Hz	100-240 VAC full range, 50-60 Hz	100-240 VAC full range, 50-60 Hz
Optional DC Power Supply	Yes	Yes	Yes
Max Power Supply	1000W	1000W	1000W
Typical, Max Power Consumption	540W, 672W	540W, 672W	540W, 672W
Weight (lbs)	48	48	48
Height	2U	2U	2U
Width	EIA 310-D, IEC 60297, DIN 41494 SC48D rack width with mounting brackets		
Depth	71.1 cm (28 in)	71.1 cm (28 in)	71.1 cm (28 in)
Operating Temperature	0-45°C (32-113°F)	0-45°C (32-113°F)	0-45°C (32-113°F)
Allowed Relative Humidity	5%-95%, Non-condensing	5%-95%, Non-condensing	5%-95%, Non-condensing
Safety Certifications	IEC 60950-1, 2nd Edition; CSA 60950-1, 2nd Edition; UL 60950-1, 2nd Edition; AS/NZS 60950-1		
Electromagnetic Emissions Certifications & Susceptibility Standard	US (FCC (Part 15 Class A)), Europe (CE (EN 55032/55024)), Australia (RCM), Japan (VCCI), Korea (KCC), Taiwan (BSMI), China (CCC), India (BIS), Russia (CUTR), Russia (EAC), Saudi Arabia (CITC), Brazil (Anatel), South Africa (ICASA), Mexico (NOM), Egypt (NTRA), Israel (MoC)		
Regulatory Compliance	RoHS, WEEE, REACH		
Citrix Compliance Regulatory Model	2U1P1D	2U1P1D	2U1P1D

1. Published Ethernet interfaces compliant per IEEE802.3-2002/2005/2008/2012.

2. Performance varies depending on ciphers deployed. Contact your Citrix sales representative for details.

Citrix ADC Platform	MPX/SDX 15120-50G	MPX/SDX 15100-50G	MPX/SDX 15080-50G
Attributes			
Memory	128 GB	128 GB	128 GB
Ethernet Ports ¹	4x 50GE QSFP28; 8x 10GE SFP+		
Transceivers Support	50GE QSFP28 Port: 50GE/100GE QSFP28: SR4; 40GE QSFP+: SR4; 25GE SFP28: SR (Adapter required); 10GE SFP+: SR, LR (Adapter required); 10GE SFP+ Port: 10GE SFP+: SR, LR		
RAID Support	Yes	Yes	Yes
Pay-as-you-grow & Burst Pack License Upgrades	-	Upgrade option to MPX/SDX 15120-50G	Upgrade option to MPX/SDX 15120, 100-50G
Performance			
System Throughput (Gbps) [L7 Throughput]	120	100	80
L7 HTTP Requests/sec	4,000,000	4,000,000	3,900,000
SSL Transactions/sec (2K Key Certificates) ²	160,000	140,000	127,000
ECDHE Transactions/sec	65,000	58,000	53,000
SSL Throughput (Gbps)	74	70	60
Compression Throughput (Gbps)	10.8	10	9.3
ICA Proxy/SSL VPN Concurrent Users	20,000	20,000	20,000
Included Instances, Maximum Instances (on SDX Platforms)	55, 55	50, 55	45, 55
Mechanical, Environmental, and Regulatory			
Power Supplies	2	2	2
Input Voltage, Frequency Range	100-240 VAC full range, 50-60 Hz	100-240 VAC full range, 50-60 Hz	100-240 VAC full range, 50-60 Hz
Optional DC Power Supply	Yes	Yes	Yes
Max Power Supply	522W	522W	522W
Typical, Max Power Consumption	300W, 1024 BTU/Hr	300W, 1024 BTU/Hr	300W, 1024 BTU/Hr
Weight (lbs)	39	39	39
Height	2U	2U	2U
Width	EIA 310-D, IEC 60297, DIN 41494 SC48D rack width with mounting brackets		
Depth	71.1 cm (28 in)	71.1 cm (28 in)	71.1 cm (28 in)
Operating Temperature	0-45°C (32-113°F)	0-45°C (32-113°F)	0-45°C (32-113°F)
Allowed Relative Humidity	5%-95%, Non-condensing	5%-95%, Non-condensing	5%-95%, Non-condensing
Safety Certifications	IEC 60950-1, 2nd Edition; CSA 60950-1, 2nd Edition; UL 60950-1, 2nd Edition; AS/NZS 60950-1		
Electromagnetic Emissions Certifications & Susceptibility Standard	US (FCC (Part 15 Class A)), Europe (CE (EN 55032/55024)), Australia (RCM), Japan (VCCI), Korea (KCC), Taiwan (BSMI), China (CCC), India (BIS), Russia (CUTR), Russia (EAC), Saudi Arabia (CITC), Brazil (Anatel), South Africa (ICASA), Mexico (NOM), Egypt (NTRA), Israel (MoC)		
Regulatory Compliance	RoHS, WEEE, REACH		
Citrix Compliance Regulatory Model	2U1P1A	2U1P1A	2U1P1A

1. Published Ethernet interfaces compliant per IEEE802.3-2002/2005/2008/2012.

2. Performance varies depending on ciphers deployed. Contact your Citrix sales representative for details.

Citrix ADC Platform	MPX/SDX 15060-50G	MPX/SDX 15040-50G
Attributes		
Memory	128 GB	128 GB
Ethernet Ports ¹	4x 50GE QSFP28; 8x 10GE SFP+	
Transceivers Support	50GE QSFP28 Port: 50GE/100GE QSFP28: SR4; 40GE QSFP+: SR4; 25GE SFP28: SR (Adapter required); 10GE SFP+: SR, LR (Adapter required); 10GE SFP+ Port: 10GE SFP+: SR, LR	
RAID Support	Yes	Yes
Pay-as-you-grow & Burst Pack License Upgrades	Upgrade option to MPX/SDX 15120, 100, 80-50G	Upgrade option to MPX/SDX 15120, 100, 80, 60-50G
Performance		
System Throughput (Gbps) [L7 Throughput]	60	40
L7 HTTP Requests/sec	3,200,000	3,000,000
SSL Transactions/sec (2K Key Certificates) ²	110,000	66,000
ECDHE Transactions/sec	45,000	28,000
SSL Throughput (Gbps)	50	40
Compression Throughput (Gbps)	8.5	7.8
ICA Proxy/SSL VPN Concurrent Users	20,000	20,000
Included Instances, Maximum Instances (on SDX Platforms)	40, 55	30, 55
Mechanical, Environmental, and Regulatory		
Power Supplies	2	2
Input Voltage, Frequency Range	100-240 VAC full range, 50-60 Hz	100-240 VAC full range, 50-60 Hz
Optional DC Power Supply	Yes	Yes
Max Power Supply	522W	522W
Typical, Max Power Consumption	300W, 1024 BTU/Hr	300W, 1024 BTU/Hr
Weight (lbs)	39	39
Height	2U	2U
Width	EIA 310-D, IEC 60297, DIN 41494 SC48D rack width with mounting brackets	
Depth	72 cm (28.3 in)	72 cm (28.3 in)
Operating Temperature	0-45°C (32-113°F)	0-45°C (32-113°F)
Allowed Relative Humidity	5%-95%, Non-condensing	5%-95%, Non-condensing
Safety Certifications	IEC 60950-1, 2nd Edition; CSA 60950-1, 2nd Edition; UL 60950-1, 2nd Edition; AS/NZS 60950-1	
Electromagnetic Emissions Certifications & Susceptibility Standard	US (FCC (Part 15 Class A)), Europe (CE (EN 55032/55024)), Australia (RCM), Japan (VCCI), Korea (KCC), Taiwan (BSMI), China (CCC), India (BIS), Russia (CUTR), Russia (EAC), Saudi Arabia (CITC), Brazil (Anatel), South Africa (ICASA), Mexico (NOM), Egypt (NTRA), Israel (MoC)	
Regulatory Compliance	RoHS, WEEE	RoHS, WEEE, REACH
Citrix Compliance Regulatory Model	2U1P1A	2U1P1A

1. Published Ethernet interfaces compliant per IEEE802.3-2002/2005/2008/2012.

2. Performance varies depending on ciphers deployed. Contact your Citrix sales representative for details.

Citrix ADC Platform	MPX/SDX 15030-50G	MPX/SDX 15020-50G
Attributes		
Memory	128 GB	128 GB
Ethernet Ports ¹	4x 50GE QSFP28; 8x 10GE SFP+	
Transceivers Support	50GE QSFP28 Port: 50GE/100GE QSFP28: SR4; 40GE QSFP+: SR4; 25GE SFP28: SR (Adapter required); 10GE SFP+: SR, LR (Adapter required); 10GE SFP+ Port: 10GE SFP+: SR, LR	
RAID Support	Yes	Yes
Pay-as-you-grow & Burst Pack License Upgrades	Upgrade option to MPX/SDX 15120, 100, 80, 60, 40-50G	Upgrade option to MPX/SDX 15120, 100, 80, 60, 40, 30-50G
Performance		
System Throughput (Gbps) [L7 Throughput]	30	20
L7 HTTP Requests/sec	2,800,000	2,500,000
SSL Transactions/sec (2K Key Certificates) ²	42,000	24,000
ECDHE Transactions/sec	20,000	10,000
SSL Throughput (Gbps)	30	20
Compression Throughput (Gbps)	7.2	6.4
ICA Proxy/SSL VPN Concurrent Users	20,000	20,000
Included Instances, Maximum Instances (on SDX Platforms)	20, 55	5, 55
Mechanical, Environmental, and Regulatory		
Power Supplies	2	2
Input Voltage, Frequency Range	100-240 VAC full range, 50-60 Hz	100-240 VAC full range, 50-60 Hz
Optional DC Power Supply	Yes	Yes
Max Power Supply	522W	522W
Typical, Max Power Consumption	300W, 1024 BTU/Hr	300W, 1024 BTU/Hr
Weight (lbs)	39	39
Height	2U	2U
Width	EIA 310-D, IEC 60297, DIN 41494 SC48D rack width with mounting brackets	
Depth	72 cm (28.3 in)	72 cm (28.3 in)
Operating Temperature	0-45°C (32-113°F)	0-45°C (32-113°F)
Allowed Relative Humidity	5%-95%, Non-condensing	5%-95%, Non-condensing
Safety Certifications	IEC 60950-1, 2nd Edition; CSA 60950-1, 2nd Edition; UL 60950-1, 2nd Edition; AS/NZS 60950-1	
Electromagnetic Emissions Certifications & Susceptibility Standard	US (FCC (Part 15 Class A)), Europe (CE (EN 55032/55024)), Australia (RCM), Japan (VCCI), Korea (KCC), Taiwan (BSMI), China (CCC), India (BIS), Russia (CUTR), Russia (EAC), Saudi Arabia (CITC), Brazil (Anatel), South Africa (ICASA), Mexico (NOM), Egypt (NTRA), Israel (MoC)	
Regulatory Compliance	RoHS, WEEE, REACH	RoHS, WEEE
Citrix Compliance Regulatory Model	2U1P1A	2U1P1A

1. Published Ethernet interfaces compliant per IEEE802.3-2002/2005/2008/2012.

2. Performance varies depending on ciphers deployed. Contact your Citrix sales representative for details.

Citrix ADC Platform	MPX/SDX 15120	MPX/SDX 15100	MPX/SDX 15080
Attributes			
Memory	128 GB	128 GB	128 GB
Ethernet Ports ¹	16x 25GE SFP28	16x 25GE SFP28	16x 25GE SFP28
Transceivers Support	25GE SFP28: SR; 10GE SFP+: SR, LR		
RAID Support	Yes	Yes	Yes
Pay-as-you-grow & Burst Pack License Upgrades	-	Upgrade option to MPX/SDX 15120	Upgrade option to MPX/SDX 15120, 15100
Performance			
System Throughput (Gbps) [L7 Throughput]	120	100	80
L7 HTTP Requests/sec	3,900,000	3,600,000	3,500,000
SSL Transactions/sec (2K Key Certificates) ²	160,000	140,000	127,000
ECDHE Transactions/sec	65,000	58,000	53,000
SSL Throughput (Gbps)	74	70	60
Compression Throughput (Gbps)	10.8	10.5	9.3
ICA Proxy/SSL VPN Concurrent Users	20,000	20,000	20,000
Included Instances, Maximum Instances (on SDX Platforms)	55, 55	50, 55	45, 55
Mechanical, Environmental, and Regulatory			
Power Supplies	2	2	2
Input Voltage, Frequency Range	100-240 VAC full range, 50-60 Hz	100-240 VAC full range, 50-60 Hz	100-240 VAC full range, 50-60 Hz
Optional DC Power Supply	Yes	Yes	Yes
Max Power Supply	1000W	1000W	1000W
Typical, Max Power Consumption	310W, 420W	310W, 420W	310W, 420W
Weight (lbs)	60	60	60
Height	2U	2U	2U
Width	EIA 310-D for 19 inch racks		
Depth	71.1 cm (28 in)	71.1 cm (28 in)	71.1 cm (28 in)
Operating Temperature	0-45°C (32-113°F)	0-45°C (32-113°F)	0-45°C (32-113°F)
Allowed Relative Humidity	5%-95%, Non-condensing	5%-95%, Non-condensing	5%-95%, Non-condensing
Safety Certifications	IEC 60950-1, 2nd Edition; CSA 60950-1, 2nd Edition; UL 60950-1, 2nd Edition; AS/NZS 60950-1		
Electromagnetic Emissions Certifications & Susceptibility Standard	US (FCC (Part 15 Class A)), Europe (CE (EN 55032/55024)), Australia (RCM), Japan (VCCI), Korea (KCC), Taiwan (BSMI), China (CCC), India (BIS), Russia (CUTR), Russia (EAC), Saudi Arabia (CITC), Brazil (Anatel), South Africa (ICASA), Mexico (NOM), Egypt (NTRA), Israel (MoC)		
Regulatory Compliance	RoHS, WEEE, REACH		
Citrix Compliance Regulatory Model	2U1P1A	2U1P1A	2U1P1A

1. Published Ethernet interfaces compliant per IEEE802.3-2002/2005/2008/2012.

2. Performance varies depending on ciphers deployed. Contact your Citrix sales representative for details.

Citrix ADC Platform	MPX/SDX 15060	MPX/SDX 15040
Attributes		
Memory	128 GB	128 GB
Ethernet Ports ¹	16x 25GE SFP28	16x 25GE SFP28
Transceivers Support	25GE SFP28: SR; 10GE SFP+: SR, LR	
RAID Support	Yes	Yes
Pay-as-you-grow & Burst Pack License Upgrades	Upgrade option to MPX/SDX 15120, 15100, 15080	Upgrade option to MPX/SDX 15120, 15100, 15080, 15060
Performance		
System Throughput (Gbps) [L7 Throughput]	60	40
L7 HTTP Requests/sec	3,200,000	3,000,000
SSL Transactions/sec (2K Key Certificates) ²	110,000	66,000
ECDHE Transactions/sec	45,000	28,000
SSL Throughput (Gbps)	50	40
Compression Throughput (Gbps)	8.5	7.8
ICA Proxy/SSL VPN Concurrent Users	20,000	20,000
Included Instances, Maximum Instances (on SDX Platforms)	40, 55	30, 55
Mechanical, Environmental, and Regulatory		
Power Supplies	2	2
Input Voltage, Frequency Range	100-240 VAC full range, 50-60 Hz	100-240 VAC full range, 50-60 Hz
Optional DC Power Supply	Yes	Yes
Max Power Supply	1000W	1000W
Typical, Max Power Consumption	310W, 420W	310W, 420W
Weight (lbs)	60	60
Height	2U	2U
Width	EIA 310-D for 19 inch racks	
Depth	71.1 cm (28 in)	71.1 cm (28 in)
Operating Temperature	0-45°C (32-113°F)	0-45°C (32-113°F)
Allowed Relative Humidity	5%-95%, Non-condensing	5%-95%, Non-condensing
Safety Certifications	IEC 60950-1, 2nd Edition; CSA 60950-1, 2nd Edition; UL 60950-1, 2nd Edition; AS/NZS 60950-1	
Electromagnetic Emissions Certifications & Susceptibility Standard	US (FCC (Part 15 Class A)), Europe (CE (EN 55032/55024)), Australia (RCM), Japan (VCCI), Korea (KCC), Taiwan (BSMI), China (CCC), India (BIS), Russia (CUTR), Russia (EAC), Saudi Arabia (CITC), Brazil (Anatel), South Africa (ICASA), Mexico (NOM), Egypt (NTRA), Israel (MoC)	
Regulatory Compliance	RoHS, WEEE, REACH	
Citrix Compliance Regulatory Model	2U1P1A	2U1P1A

1. Published Ethernet interfaces compliant per IEEE802.3-2002/2005/2008/2012.

2. Performance varies depending on ciphers deployed. Contact your Citrix sales representative for details.

Citrix ADC Platform	MPX/SDX 15030	MPX/SDX 15020
Attributes		
Memory	128 GB	128 GB
Ethernet Ports ¹	16x 25GE SFP28	16x 25GE SFP28
Transceivers Support	25GE SFP28: SR; 10GE SFP+: SR, LR	
RAID Support	Yes	Yes
Pay-as-you-grow & Burst Pack License Upgrades	Upgrade option to MPX/SDX 15120, 15100, 15080, 15060, 15040	Upgrade option to MPX/SDX 15120, 15100, 15080, 15060, 15040, 15030
Performance		
System Throughput (Gbps) [L7 Throughput]	30	20
L7 HTTP Requests/sec	2,800,000	2,500,000
SSL Transactions/sec (2K Key Certificates) ²	42,000	24,000
ECDHE Transactions/sec	20,000	10,000
SSL Throughput (Gbps)	30	20
Compression Throughput (Gbps)	7.2	6.4
ICA Proxy/SSL VPN Concurrent Users	20,000	20,000
Included Instances, Maximum Instances (on SDX Platforms)	20, 55	5, 55
Mechanical, Environmental, and Regulatory		
Power Supplies	2	2
Input Voltage, Frequency Range	100-240 VAC full range, 50-60 Hz	100-240 VAC full range, 50-60 Hz
Optional DC Power Supply	Yes	Yes
Max Power Supply	1000W	1000W
Typical, Max Power Consumption	310W, 420W	310W, 420W
Weight (lbs)	60	60
Height	2U	2U
Width	EIA 310-D for 19 inch racks	
Depth	71.1 cm (28 in)	71.1 cm (28 in)
Operating Temperature	0-45°C (32-113°F)	0-45°C (32-113°F)
Allowed Relative Humidity	5%-95%, Non-condensing	5%-95%, Non-condensing
Safety Certifications	IEC 60950-1, 2nd Edition; CSA 60950-1, 2nd Edition; UL 60950-1, 2nd Edition; AS/NZS 60950-1	
Electromagnetic Emissions Certifications & Susceptibility Standard	US (FCC (Part 15 Class A)), Europe (CE (EN 55032/55024)), Australia (RCM), Japan (VCCI), Korea (KCC), Taiwan (BSMI), China (CCC), India (BIS), Russia (CUTR), Russia (EAC), Saudi Arabia (CITC), Brazil (Anatel), South Africa (ICASA), Mexico (NOM), Egypt (NTRA), Israel (MoC)	
Regulatory Compliance	RoHS, WEEE, REACH	
Citrix Compliance Regulatory Model	2U1P1A	2U1P1A

1. Published Ethernet interfaces compliant per IEEE802.3-2002/2005/2008/2012.

2. Performance varies depending on ciphers deployed. Contact your Citrix sales representative for details.

Citrix ADC Platform	MPX/SDX 8930	MPX/SDX 8920
Attributes		
Memory	32 GB	32 GB
Ethernet Ports ¹	4x 10GE SFP+; 6x 10/100/1000 CU	
Transceivers Support	10GE SFP+: SR, LR	
RAID Support	No	No
Pay-as-you-grow & Burst Pack License Upgrades	-	Upgrade option to MPX/SDX 8930
Performance		
System Throughput (Gbps) [L7 Throughput]	33	20
L7 HTTP Requests/sec	2,300,000	1,700,000
SSL Transactions/sec (2K Key Certificates) ²	40,000	22,000
ECDHE Transactions/sec ⁴	16,000	10,000
SSL Throughput (Gbps)	25	20
Compression Throughput (Gbps)	4.8	4
ICA Proxy/SSL VPN Concurrent Users	10,000	10,000
Included Instances, Maximum Instances (on SDX Platforms)	2, 7	2, 7
Mechanical, Environmental, and Regulatory		
Power Supplies	1 (2nd optional)	1 (2nd optional)
Input Voltage, Frequency Range	100-240 VAC full range, 50-60 Hz	100-240 VAC full range, 50-60 Hz
Optional DC Power Supply	Yes	Yes
Max Power Supply	275W	275W
Typical, Max Power Consumption	225W	225W
Weight (lbs)	25	25
Height	1U	1U
Width	EIA 310-D for 19 inch racks	
Depth	61 cm (24 in)	61 cm (24 in)
Operating Temperature	0-45°C (32-113°F)	0-45°C (32-113°F)
Allowed Relative Humidity	5%-95%, Non-condensing	5%-95%, Non-condensing
Safety Certifications	CSA	
Electromagnetic Emissions Certifications & Susceptibility Standard	FCC, CE, VCCI, RCM, CCC, KCC, BIS, NOM, CITC, ICASA, EAC	
Regulatory Compliance	RoHS, WEEE, REACH	
Citrix Compliance Regulatory Model	1U1P1A	1U1P1A

1. Published Ethernet interfaces compliant per IEEE802.3-2002/2005/2008/2012.

2. Performance varies depending on ciphers deployed. Contact your Citrix sales representative for details.

Citrix ADC Platform	MPX 8910	MPX 8905
Attributes		
Memory	32 GB	32 GB
Ethernet Ports ¹	4x 10GE SFP+; 6x 10/100/1000 CU	
Transceivers Support	10GE SFP+: SR, LR	
RAID Support	No	No
Pay-as-you-grow & Burst Pack License Upgrades	Upgrade option to MPX 8930, 8920	Upgrade option to MPX 8930, 8920, 8910
Performance		
System Throughput (Gbps) [L7 Throughput]	10	5
L7 HTTP Requests/sec	1,400,000	990,000
SSL Transactions/sec (2K Key Certificates) ²	13,000	8,000
ECDHE Transactions/sec ⁴	6,000	4,000
SSL Throughput (Gbps)	10	5
Compression Throughput (Gbps)	3.5	2.5
ICA Proxy/SSL VPN Concurrent Users	10,000	10,000
Included Instances, Maximum Instances (on SDX Platforms)	N/A	N/A
Mechanical, Environmental, and Regulatory		
Power Supplies	1 (2nd optional)	1 (2nd optional)
Input Voltage, Frequency Range	100-240 VAC full range, 50-60 Hz	100-240 VAC full range, 50-60 Hz
Optional DC Power Supply	Yes	Yes
Max Power Supply	275W	275W
Typical, Max Power Consumption	225W	225W
Weight (lbs)	25	25
Height	1U	1U
Width	EIA 310-D for 19 inch racks	
Depth	61 cm (24 in)	61 cm (24 in)
Operating Temperature	0-45°C (32-113°F)	0-45°C (32-113°F)
Allowed Relative Humidity	5%-95%, Non-condensing	5%-95%, Non-condensing
Safety Certifications	CSA	
Electromagnetic Emissions Certifications & Susceptibility Standard	FCC, CE, VCCI, RCM, CCC, KCC, BIS, NOM, CITC, ICASA, EAC	
Regulatory Compliance	RoHS, WEEE, REACH	
Citrix Compliance Regulatory Model	1U1P1A	1U1P1A

1. Published Ethernet interfaces compliant per IEEE802.3-2002/2005/2008/2012.

2. Performance varies depending on ciphers deployed. Contact your Citrix sales representative for details.

Citrix ADC Platform	MPX 5910	MPX 5905	MPX 5901
Attributes			
Memory	16 GB	16 GB	16 GB
Ethernet Ports ¹	2x 10GE SFP; 6x 10/100/1000 CU		
Transceivers Support	10GE SFP+: SR, LR; 1GE SFP: CU		
RAID Support	No	No	No
Pay-as-you-grow & Burst Pack License Upgrades	-	Upgrade option to MPX 5910	Upgrade option to MPX 5910, 5905
Performance			
System Throughput (Gbps) [L7 Throughput]	10	5	1
L7 HTTP Requests/sec	900,000	700,000	400,000
SSL Transactions/sec (2K Key Certificates) ²	12,000	6,000	4,000
ECDHE Transactions/sec	6,000	3,000	1,700
SSL Throughput (Gbps)	8	5	1
Compression Throughput (Gbps)	2.5	1.5	1
ICA Proxy/SSL VPN Concurrent Users	5,000	5,000	5,000
Included Instances, Maximum Instances (on SDX Platforms)	N/A	N/A	N/A
Mechanical, Environmental, and Regulatory			
Power Supplies	1 (2nd optional)	1 (2nd optional)	1 (2nd optional)
Input Voltage, Frequency Range	100-240 VAC full range	100-240 VAC full range	100-240 VAC full range
Optional DC Power Supply	Yes	Yes	Yes
Max Power Supply	366W	366W	366W
Typical, Max Power Consumption	300W, 840 BTU/Hr	300W, 840 BTU/Hr	300W, 840 BTU/Hr
Weight (lbs)	25	25	25
Height	1U	1U	1U
Width	EIA 310-D for 19 inch racks		
Depth	61 cm (24 in)	61 cm (24 in)	61 cm (24 in)
Operating Temperature	0-45°C (32-113°F)	0-45°C (32-113°F)	0-45°C (32-113°F)
Allowed Relative Humidity	5%-95%, Non-condensing	5%-95%, Non-condensing	5%-95%, Non-condensing
Safety Certifications	CSA		
Electromagnetic Emissions Certifications & Susceptibility Standard	FCC, CE, VCCI, RCM, CCC, KCC, BIS, NOM, CITC, ICASA, EAC		
Regulatory Compliance	RoHS, WEEE, REACH		
Citrix Compliance Regulatory Model	1U1P1A	1U1P1A	1U1P1A

1. Published Ethernet interfaces compliant per IEEE802.3-2002/2005/2008/2012.

2. Performance varies depending on ciphers deployed. Contact your Citrix sales representative for details.

Technical Aspects

Citrix Gateway

- Provides consolidation of secure remote access infrastructure with one URL
- Provides SAML 2.0 federated identity to provide single sign-on (SSO) across all applications, whether in a data center or in a cloud
- One URL to access any application
- AlwaysON allows auto-reconnect of SSL VPN session when users are moving between networks
- AlwaysON VPN allows to establish a VPN connection before Windows logon that help admin manage the laptop remotely
- Integration with StoreFront allows importing UI changes from StoreFront to Gateway portal and vice versa
- Gateway Insight for monitoring and troubleshooting all Gateway traffic for issues like authentication, EPA, single sign-on failures, etc.
- nFactor authentication for all applications
- Stateless RDP proxy
- Support for Linux (Ubuntu 18 and 16.04)
- Support for Mac (OS X 10.14, OS X 10.15)
- Support for Windows 10, 8, 8.1 and 7 (32bit / 64bit)
- Support for iOS 12 or later. Compatible with iPhone, iPad, and iPod touch.
- Support for Android 7.0 and later

Secure Access

- Citrix Virtual Apps and Desktops and Citrix Endpoint Management, formerly XenMobile, integration
- Device certificate scanning
- Single sign-on using NTLM/Kerberos/SAML, etc.
- SmartAccess: Adaptive application and action control enforced on Citrix Virtual Apps and Desktops servers
- SmartControl: Adaptive application and action control enforced on Citrix Gateway, thereby providing centralized policy management and security at the edge
- Integrated Citrix Gateway SSL VPN

- For ADC versions after 11.1, the Standard edition includes (500) Universal licenses, Enterprise or Advanced editions include (1000) Universal licenses, and there are no Universal license requirements with Platinum or Premium editions. For versions previous to Citrix ADC 11.1, the Standard and Enterprise editions include (5) Universal licenses, and the Platinum edition includes (100) Universal licenses.
- Endpoint analysis of user device
- SAML 2.0 and nFactor; passwords for single sign on to applications running behind Citrix Gateway
- AAA traffic management
- SAML 2.0 and NTLMv1/2 support for configuring ADC with single sign-on (SSO)
- Support for Active Directory, LDAP, RADIUS, TACACS+, OCSP, Diameter, etc.

L4-7 Traffic Management

Layer 4 Load Balancing (LB)

- Protocols supported: TCP, UDP, FTP, HTTP, HTTPS, DNS (TCP and UDP), SIP (over UDP), RTSP, RADIUS, Diameter, SQL, RDP, IS-IS, SMPP
- Algorithms: Round Robin, Least Packets, Least Bandwidth, Least Connections, Response Time, Hashing (URL, Domain, Source IP, Destination IP, and CustomID), SNMP-provided metric, Server Application State Protocol (SASP)
- Session persistence: Source IP, cookie, server, group, SSL session, SIP CALLID, Token-based, SESSIONID, Diameter AVP
- Session protocols: TCP, UDP, SSL_TCP, Multi-path TCP, SPDY
- Server monitoring: Ping, TCP, URL, ECV, scriptable health checks, Dynamic Server Response Time
- Link load balancing

Layer 7 Content Switching

- Policies: URL, URL Query, URL Wildcard, Domain, Source/ Destination IP, HTTP Header, Custom, HTTP and TCP Payload Values, UDP, Diameter AVP
- Switch requests based on protocol of incoming packets

Database Load Balancing

- Support for Microsoft SQL Server and MySQL
- Switching algorithms include SQL query parameters such as user and database names and command parameters
- Token-based load balancing provides advanced configuration for persistence and fault-tolerant deployments

TriScale Clustering²

- inScale-Outin with clustering up to 32 Citrix ADC appliances into single system image and up to 3 Tbps throughput
- Configuration Coordinator node for centralized management and synchronization
- Compatible with Pay-As-You-Grow and Burst Pack performance upgrades
- Traffic distribution mechanisms include: Equal Cost Multiple Path (ECMP), Link- sets, and Cluster Link Aggregation Group (CLAG)
- Available on Citrix ADC MPX, SDX, and VPX
- Modules may be configured on all nodes in a cluster or using “spotted VIPS,” in which they are added only to a select subset of nodes

e-based Policy Enforcement

- Trigger ADC policies based upon connections per second, packets per second, or bandwidth used
- Source or destination-based upon header or payload information

Traffic Domains

- Allows overlapping IP addresses
- Provides separate routing flows within a single appliance
- Enables basic multi-tenancy implementations

Admin Partitioning

- Independent instances that share resources on the appliance
- Maximum number of 512 admin partitions per appliance

Global Server Load Balancing (GSLB)

- Algorithms: site health, geographic proximity, network proximity, connections, bandwidth, AG-E SSL, VPN users
- Site health checking on status, connection load, packet rate, SNMP-provided metrics

Surge Protection and Priority Queuing²

- Adaptive rate control for TCP connections and HTTP requests
- Prioritized transaction dispatch for critical application requests

Carrier-grade Network Address Translation²

- Support for: Full-cone NAT, Deterministic NAT, Endpoint-Independent Mapping and Filtering, Hairpinning
- Application Layer Gateways: FTP, TFTP, ICMP, SIP, RTSP, PPTP, GRE

Subscriber-aware Traffic Steering

- Policy control interface: Gx, RADIUS

Application Acceleration

TCP Optimization

- Multiplexing, buffering, connection keep-alive, windows scaling, selective acknowledgement, fast ramp, TCP Westwood
- AppCompress
- Gzip-based compression for HTTP traffic AppCache³
- Caching for static and dynamic application content
- HTTP GET and POST method support
- Policies defined based upon HTTP header and body values

Application Security

DoS Attack Defense

- Continue service to legitimate users while protecting against attacks such as SYN Flood, HTTP DoS, and Ping of Death
- ICMP and UDP rate control

Content Rewriting and Response Control

- Policy-based bidirectional rewriting of HTTP header and payload elements
- Policy-based redirection of incoming requests
- Body URL rewrite
- Responder module
- Custom responses and redirects
- Policy-based routing
- Network aware policies

SSL Encryption

- Supports Thales nShield and SafeNet HSM integration

DNSSEC

- DNS proxy
- Authoritative DNS
- DNS signing

Packet Filtering

- Layer 3 and 4 Access Control Lists (ACL)
- Network Address Translation (NAT)
- IPv4/IPv6 Network Address Translation (NAT)

Citrix Web App Firewall with Hybrid Security Model³

- Positive security model protects against: buffer overflow, CGI- BIN parameter manipulation, form/hidden field manipulation, forceful browsing, cookie or session poisoning, broken ACLs, cross-site scripting (XSS), command injection, SQL injection, error triggering sensitive information leak, insecure use of cryptography, server misconfiguration, back doors and debug options, rate-based policy enforcement, well known platform vulnerabilities, zero-day exploits,

- cross site request forgery (CSRF), credit card and other sensitive data leakage prevention
- Negative security model with automatically updated signatures to protect against L7 and HTTP application vulnerabilities
- Integrates with third-party scanning tools
- Common event format (CEF) logs
- XML security: XML denial of service (xDoS)
- XML SQL injection and cross site scripting, XML message validation, format checks, WS-I basic profile compliance, XML, XPath injection attachment check, xQuery Injection protection
- WSDL scan prevention
- Attachment checks
- URL transformation
- Cookie proxy and encryption
- SOAP array attack protection

IP Reputation Service

- Enhanced service that provides a continuously updated list of malicious IP addresses in near realtime

Cloud Connector for Citrix Networking³

- Network connectivity protection via IPSec security
- Datacenter extension through GRE-based network bridging

Support for Citrix Endpoint Management MDM⁵

- Front end optimization scalable to over 100,000 concurrent users
- Citrix Gateway connector for Exchange ActiveSync provides a device level authorization service
- Application level policy controlled SSL VPN tunneling for mobile clients

Network Integration

- Static routes, monitored static routes, weighted static routes
- OSPF, RIP1/2, BGP2
- VLAN 802.1Q
- Link Aggregation 802.3ad

- Stateful IPv6 to IPv4 network address translation and DNS64
- Static and stateless network address translation from IPv4 to IPv6

High Availability

- Active/Passive
- Active/Active
- VRRP
- ECMP
- Connection mirroring

Simplified Installation and Management

User Interface

- Graphical application visualizer
- Secure web-based GUI
- CLI, Telnet, SSH, Console
- Real-time performance dashboard
- LB, GSLB Application Firewall and configuration wizards for monitoring
- Citrix Virtual Apps configuration wizards

Policy Management

- AppExpert Visual Policy Builder
- Policy extensibility via HTTP service callouts
- AppExpert templates
- AppExpert Visualizers

Command Center

- Centralized configuration and management of over 200 Citrix ADC appliances

Citrix Application Delivery Management (ADM)

- Citrix ADM is a software solution enabling traffic visibility; it includes HDX Insight and Web Insight and is based on AppFlow
- HDX Insight parses ICA sessions to provide troubleshooting, network analysis, and end-to-end performance for Citrix Virtual Apps and Desktops sessions. Historical data included in Premium Edition.

- Web Insight monitors real-time web application traffic and assists capacity planning and helps ensure SLAs
- AppFlow Standards-based NetFlow/IPFIX (Internet Protocol Flow Information Export) solution
- Supported by leading performance monitoring and management vendors
- Provides transaction level visibility for HTTP, SSL, TCP, and SSL/TCP flows

Action Analytics

- Aggregates real-time traffic statistics and enables their use in setting dynamic policies
- Charting and analysis utilities using HDX Insight

Third-party Management Support

- SNMPv1, SNMPv2, and SNMPv3: Citrix ADC MIB and MIB-II support
- Microsoft System Center Operations Management (SCOM) support
- Comtrade support with Management Pack for Citrix ADC
- Microsoft System Center Virtual Machine Manager (SCVMM) support
- XML/SOAP API for automated application-driven configuration

Real-time Consolidated Logging

- Offloads logging from application server to a central location

Native Web Interface

- Integrated Web Interface Server for Citrix Virtual Apps and Desktops
- Supports JAVA environments with MPX and VPX platforms running Citrix ADC nCore OS
- Authentication methods include: LDAP, RADIUS, NTLM, TACACS+, Client Certificate
- Manage HTTPS requests via included SSL VPN
- Wizards-based configuration through Citrix ADC GUI
- Login page customization
- Includes Smart Access, smooth roaming, STA server redundancy, and session reliability

Lower Total Cost of Ownership

Web Cache Redirection²

- Automatically direct requests with content not cached on ADC to cache farm
- N-tier multilayer load balancing support of cache servers

1. Additional ADC packs with 3 (8xxx) or 5 (all other models) instances each are available. For SDX 8015, the maximum number of instances is 5.

2. Available in ADC Advanced and Premium editions only.

3. Included in Premium edition only; not available with Standard or Advanced editions.

4. Available as a license upgrade on all editions and for MPX, SDX (excluding 22000 series), and VPX appliances.

5. Advanced edition with AppCache or Premium edition recommended.



Enterprise Sales

North America | 800-424-8749

Worldwide | +1 408-790-8000

Locations

Corporate Headquarters | 851 Cypress Creek Road, Fort Lauderdale, FL 33309, United States

Silicon Valley | 4988 Great America Parkway, Santa Clara, CA 95054, United States

©2020 Citrix Systems, Inc. All rights reserved. Citrix, the Citrix logo, and other marks appearing herein are property of Citrix Systems, Inc. and/or one or more of its subsidiaries, and may be registered with the U.S. Patent and Trademark Office and in other countries. All other marks are the property of their respective owner(s).